



ND150 Cleaning Hatch is designed to be installed on IBC's and static tanks intended for chemical and foodstuff liquid products.

### SPECIFICATION

Nominal diameter	154 mm (6")
Weight	8 Kg
Fastening points	3
Working Pressure	4 Bar
Test Pressure	6 Bar
Working Temperature	-40° to +200°C

Temperature range may vary according to the seal material

### CONFORMITY, CERTIFICATION & APPROVAL

ADR / RID / IMDG / ASME / EN14025

### ACCESSORIES

Coverlid	11 18 94 10 02
Coverlid kit (coverlid, seal, pins & bolts)	11 18 94 90 00
Coverlid seal	11 13 91 10 02
Neckring	11 13 91 10 00

### STANDARD FEATURES

Made of (material)	316L / 1.4404/1.4409 st. steel manlid
Seal material	Black Nitrile / EPDM-PTFE
Neckring height	120 mm
Neckring thickness	7 mm
Fastening	3 Swingbolts with captive wing nuts
Perfect tightness	Trapezoidal seal groove - Seal 14x10

### CODIFICATION

Full ND150 Cleaning Hatch - Design pressure 4 Bar - 316L/1.4404 stainless steel - black nitrile seal

11 18 94 00 00

### DIMENSIONAL DRAWING

