

Perolo 316L stainless steel weld-in flanges are designed to be welded on top of tank containers, IBCs, road tankers, rail tank cars and storage tanks in order to fit valves and accessories for tank filling and discharge purposes.

## SPECIFICATION

- 316L stainless steel construction
- Nominal diameter 1 1/4 "
- Radiused angles
- Serrated gasket contact area

## OPTIONS

- Other diameter weld-in flanges
- Other material (carbon steel, 304L, 904L...)
- Other drilling

If you require a gasket or bolting kit for a specific valve, please refer to the installation sheet of that valve

Part Number: 11 90 20 00 00	for ATCO ND32 ball valve
	Tank type T1 to T19
	Internal - external diameter <b>32 mm - 127 mm</b>
	Thickness <b>22 mm</b>
	Drilling <b>4 x M10 x 103.5 PCD</b>
Seal (CNAF/PTFE)	12 91 90 00 00

Part Number: 11 90 38 00 00	for ATCO ND32 ball valve
	Tank type T1 to T19
	Internal - external diameter <b>32 mm - 127 mm</b>
	Thickness <b>50 mm</b>
	Drilling <b>4 x M10 x 103.5 PCD</b>
Seal (CNAF/PTFE)	12 91 90 00 00

Part Number: 11 91 12 00 00	for ATCO ND32 ball valve - Recessed
 	Tank type T1 to T19
	Internal - external diameter <b>32mm - 166 mm</b>
	Thickness <b>min 23.5 mm, max 46 mm</b>
	Drilling <b>4 x M10 x 103.5 PCD</b>
Seal (CNAF/PTFE)	12 91 90 00 00

