

Perolo 316L stainless steel weld-in flanges are designed to be welded on top of tank containers, IBCs, road tankers, rail tank cars and storage tanks in order to fit valves and accessories for tank filling and discharge purposes.


### SPECIFICATION

- 316L stainless steel construction
- Nominal diameter 1 1/2" & 2"
- Radiused angles
- Serrated gasket contact area

If you require a gasket or bolting kit for a specific valve, please refer to the installation sheet of that valve


### OPTIONS

- Other diameter weld-in flanges
- Other material (carbon steel, 304L, 904L...)
- Other drilling

Part Number: 11 90 25 00 00	for Tankfly ND50 butterfly valve - PN16 ND50
	Tank type T1 to T19
	Internal - external diameter <b>50 mm - 165 mm</b>
	Thickness <b>26,5 mm</b>
	Drilling <b>4 x M16 x 125 PCD</b>
Seal (CNAF/PTFE)	11 90 29 00 00

Part Number: 11 92 51 00 00	PN16 ND40
	Tank type T1 to T19
	Internal - external diameter <b>49 mm - 150 mm</b>
	Thickness <b>30 mm</b>
	Drilling <b>4 x M16 x 110 PCD</b>
Seal (CNAF/PTFE)	on request

Part Number: 11 91 19 00 00	PN16 ND50 and other
	Tank type T1 to T19
	Internal - external diameter <b>50 mm - 165 mm</b>
	Thickness <b>50 mm</b>
	Drilling <b>4 x M10 x 100 PCD and 4 x M16 x 125 PCD</b>
Seal (CNAF/PTFE)	11 90 29 00 00

Part Number: 11 91 20 00 00	PN16 ND50 and other
	Tank type T1 to T19
	Internal - external diameter <b>50 mm - 165 mm</b>
	Thickness <b>59 mm</b>
	Drilling <b>4 x M10 x 100 PCD and 4 x M16 x 125 PCD</b>
Seal (CNAF/PTFE)	11 90 29 00 00

Part Number: 11 92 44 00 00	PN16 ND50 and other - Recessed
	Tank type T1 to T19
	Internal - external diameter <b>50 mm - 190 mm</b>
	Thickness <b>min. 27 mm - max 63 mm</b>
	Drilling <b>4 x M10 x 100 PCD and 4 x M16 x 125 PCD</b>
Seal (CNAF/PTFE)	11 90 29 00 00

Part Number: 12 92 21 00 00	1 1/2" ANSI 150 & PN16 ND40 - Recessed
	Tank type T1 to T19
	Internal - external diameter <b>49 mm - 166 mm</b>
	Thickness <b>min. 27 mm - max 58 mm</b>
	Drilling <b>4 x M12 x 98.4 PCD and 4 x M16 x 110 PCD</b>
Seal (CNAF/PTFE)	11 90 29 00 00

