



The 3" TANKFLY clamped butterfly valve is designed to be clamped between 2 flanges or directly onto the pipe work.

SPECIFICATION	
Nominal diameter	80 mm (3")
Weight	3.7 Kg
Inlet flange	Clamped between DIN or ANSI Flange
Outlet flange	Clamped between DIN or ANSI Flange*
Working Pressure	7 Bar
Test Pressure	10.5 Bar
Working Temperature	STD:-40° to +150°C/ HT°:-40° to 250°C
Design Temperature	-40° to +190°C/ +250°C for HT

CONFORMITY, CERTIFICATION & APPROVAL	
Comply with ADR / IMDG / RID / EN14432	
Approved by Bureau Veritas - RMR	

STANDARD FEATURES	
Made of (material)	316L / 1.4409 stainless steel
Compact Design	Face to face 48 mm
Operation	Handle - 1/4 turn with Locking
Closure plate seal	PTFE

ACCESSORIES	
Weld in flange	11 90 36 00 00
Seal	12 91 40 00 00
Adaptor flange	12 91 41 00 03
Blind flange	11 95 90 00 00
Screw kit M16-90	12 85 57 00 24
Screw kit M16-40	11 10 09 91 00
Remote control	RMT83

*for more options please check specification sheet of TP8

CODIFICATION	
3" TANKFLY flanged butterfly valve, PTFE gasket to clamp between two flanges	11 12 62 00 00 D

DIMENSIONAL DRAWING

