



The 3" CHEMFLY clamped butterfly valve is designed to be clamped between 2 flanges or directly onto the pipe work.

SPECIFICATION

Nominal diameter	80 mm (3")
Weight	3.0 Kg
Inlet flange	Clamped between DIN or ANSI Flange
Outlet flange	Clamped between DIN or ANSI Flange
Working Pressure	7 Bar
Test Pressure	10.5 Bar
Working Temperature	-40° to +150°C (HT °250°C on request)

CONFORMITY, CERTIFICATION & APPROVAL

Comply with ADR / IMDG / RID / EN14432

Approved by Bureau Veritas

ACCESSORIES

Handle locking key	17 12 01 30 00
3" BSP Outlet Nozzle	12 85 69 10 00
Bolting kit	12 85 84 91 00
Flat Gasket	12 91 42 00 00
Flat Gasket	12 91 39 00 00
Spacer set	12 85 57 91 00

STANDARD FEATURES

Made of (material)	316L / 1.4409 stainless steel
Compact Design	Face to face 47 mm
Operation	Locking Handle - 1/4 turn
Closure plate seal	PTFE

CODIFICATION

3" CHEMFLY clamped butterfly valve - standard

17 12 01 00 00

DIMENSIONAL DRAWING

